

FIG.1 PRIOR ART





250

\sim	COLOR	BLACK CYAN MAGENTA YELLOW	BLACK CYAN MAGENTA YELLOW	•••
	UPDATE	2002/07/10 2002/07/10 2002/07/10 2002/07/10	2002/09/20 2002/09/20 2002/09/20 2002/09/20	•••
	PRESCRIPTION	OIL APPLIED OIL APPLIED OIL APPLIED OIL APPLIED	OILLESS OILLESS OILLESS OILLESS	•••
	MODEL NAME	aaaa aaaa aaaa	9999 9999 9999	•••
	T NAME	A-BK A-C A-M A-Y	B-BK B-C B-M B-Y	···
	PRODUCT NAME	PRODUCT-A A-M A-Y	PRODUCT-B	•••

THERMAL PROPERTY	PROPERTY -8	4.5	5.0	5.0	4.0	
PERTY	PROPERTY -7	3.1	4.5	4.1	3.7	
ELECTRICAL PROPERTY	PROPERTY -6	36	35	32	35	
ELEC'	PROPERTY -5	1.5	1.0	3.8	0.4	
FINE-PARTICLE PROPERTY	PROPERTY -4	3.0	4.5	5.0	5.8	
DIST.	PROPERTY -3	7.8	5.7	5.5	5.5	
PARTICLE-SIZE DIS	PROPERTY PROPERTY -3	0.84	0.01	0. 45	0.39	
PART	PROPERTY -1	0.8	8.3	8.9	1.2	
PRODUCT	NAME	A-BK	A-C	A-M	A-Y	

FIG.5A




FIG.5B




FIG.6






FIG.7



THRESHOLD VALUE	DISPLAY CONTROL
OVER 25% AND UNDER 50%	IF TWO OR MORE OF "B" TO "E" DIFFER FROM "A", ALARM IS DISPLAYED.
OVER 50% AND UNDER 75%	IF THREE OR MORE OF "B" TO "E" DIFFER FROM "A", ALARM IS DISPLAYED.
OVER 75% AND UNDER 100%	IF ALL OF "B" TO "E" DIFFER FROM "A", THEN ALARM IS DISPLAYED
100%	NO ALARM IS DISPLAYED

FIG.9








FIG. 10



-10-1






FIG.14

_					_281	
□RE	EQUEST OF TE	RM R	EGISTRATION	·		
CO AP	THE FOLLOWING TERM IS NEWLY RECORDED. CORRECT THE TERM IF NEEDED. APPROVAL SCREEN WILL APPEAR IF "OK" BUTTON IS CLICKED.					
	MASTER	NE	W TERM			
	MEASURING METHOD		VERSE CHARGED TO STING METHOD	ONER		
					¥:	
	REVERSE CHARGED TONER TESTING METHOD CORRECT 283				83	
	OK CANCEL					
				\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	284	
	SELECTION OF PERSONNEL			NEL		
			EXAMINED BY	00 000	∇	
			APPROVED BY	00 000	abla	
				TRANSMIT		